

Door Access Control

C3-200

Specification



Number of Doors Controlled : 2 Door
Card Holders Capacity : 30,000
Log Events Capacity : 100,000
Communication : TCP/IP and RS-485
Number of Readers Supported : 8(4 RS-485 Reader,
4 26-bit wiegand reader)
Types of Readers Supported : 26-bit Wiegand,
others upon request
Number of Inputs : 6 (2Exit Device, 2 Door Status,
2AUX)
Number of Outputs : 4 (2-From C Relay for
Lock and 2-Form C Relay for Aux Output)
Weight : 7.5lbs (3.4kg)
Enclosure : Powder Coated Aluminium
Mounting : Wall Mount
Recommended Power Supply : 12V DC, 1.5A
Dimensions (Bundle Only) : 380mm(L)X80mm(W)
X 280mm(H)
Dimensions (Board Only) : (160mm×106mm)

Features:

- ▶ 256 time Zones, 256 access levels
- ▶ Anti-passback function
- ▶ Interlock function , Linkage function
- ▶ Multi-Card Opening function, Remote door opening and closing
- ▶ Real-Time monitoring Via Web browser
- ▶ 2 auxiliary input may be connected to infrared body detectors,
- ▶ Fire alarms, smoke detectors etc.
- ▶ 2 auxiliary output may be connected to alarms, cameras,door bells etc.
- ▶ TCP/IP and RS485 communication
- ▶ Built-in Auxiliary input and Output
- ▶ Access Control Functions
- ▶ Support full range of card readers

Software and Database Supported :

Access Security System 3.5 (Desktop Version)

Database Type:- MS Access / MS SQL