

SMART WALL LAMP IP CAMERA



FEATURES

- 2MP
- Wall lamp operation at night with bright white LEDs
- Antenna design for 100 meters long Wi-Fi connectivity
- Audio intercom with built-in omnidirectional noise reduction microphone and speaker
- Intelligent night vision modes with white & infrared LEDs
- weather IP65 housing design
- Mobile app for seamless P2P video monitoring



1080P FHD Video



SD Card



Two-Way Intercom



Cloud Recording



Wi-Fi Setup



IP 65

Technical Specification

Model	T17937
Resolution	2 Mega pixel
Image Sensor	1/2.9" COMS SC2232H
Viewing Angle	2.8 mm, Horizontal FOV : 97°, Vertical FOV : 63°, Diagonal FOV : 120°
Video Compression	H.265/20FPS, AVI format
Video Format	PAL
Minimum Illumination	Color 0.02 Lux (F2.0, VGC ON) Black & White 0.1Lux with IR
Electronic Shutter	Automatic
Wide Dynamic Range	Digital Wide Dynamic Range
Noise Reduction	3D
Infrared LED	16 SMD LEDs
White LED	32 SMD LEDs
White LED Distance	15-20Meter
Infrared LED Distance	15-20Meter
Audio	Built-in omnidirectional noise reduction microphone and speaker, support two-way real-time audio transmission, AAC audio compression standard, adaptive code stream
Alarm	Support Voice Alarm and Picture Push on mobile app
Local Storage	SD Card up to 128GB
Cloud Storage	Yes (optional)
Connection	Wired & Wireless
Network Protocol	Wi-Fi wireless transmission (support IEEE802.11b/g/n wireless protocol), RJ 45 interface (10Mbps/100Mbps adaptive) TCP/IP, UDP, HTTP, DDNS, DHCP, FTP, NTP
Power Supply	DC 12V/1A

Working Environment

Working temperature : -10°C ~ +50°C

Dimensions

Working humidity : ≤95%RH

14cm x 10cm x 12cm (L x W x Dmm)

Similar Products



Smart 3MP 4G
Robot Camera



Smart 3MP
Battery Camera



Smart 3MP Wi-Fi
Dome Camera



Smart 3MP 4G
Bullet Camera



Smart 3MP 4G
Cube Camera



Smart 3MP 4G
Mini PT Camera

* Note: Product specifications are subject to change without prior notice.