

4G Smart Linkage PT Dome Camera



FEATURES

- 2+2MP 4G Smart Linkage PT Dome Camera
- 4MM+4MM Fixed Lens
- PT Horizontal & Vertical Movement Range Pan 350°, Tilt 90°
- Dual monitoring. One camera for monitoring, One camera for PT detailed monitoring.
- Built-in high-sensitivity Mic and Speaker For Half Duplex Audio Intercom
- Support 10X Digital Zoom
- Can be set 6 preset points favorite locations
- Unique Three Smart Night Vision Modes
- Micro SD Card Up to 256GB & Cloud Storage (Optional)
- 4G Connection, QR code camera configuration with mobile/PC
- Active defense Siren & Lights
- Customized Voice Recordable message for Audio Alerts Broadcast
- Area motion detection, Humanoid detection, Push Realtime Notification on the Application
- Support monitoring: Pc / Mobile on Truecloud
- Compression: H.264/H.265
- Alexa Support



4G SIM Support



256GB SD Card



2+2MP Resolution



Digital Zoom



Auto Human Tracking



Video Compression



All Time Color



Cloud Recording



Location Presets

Technical Specifications

Image Sensor	1/2.9 2MP+2MP HD CMOS Dual Sensor
Resolution	1920 x 2160
Lens	Bullet: 4mm fixed lens PT Dome: 4mm fixed lens"
IR LEDs	Bullet : 4 Pcs PT Dome: 6 Pcs "
IR LED Distance	>30 Meters
White LEDs	Bullet : 4 Pcs
White LED Distance	PT Dome : 6 Pcs " >30 Meters
Minimum Illumination	Color : 0.1 Lux, BW : 0.01 Lux
Day & Night Mode	IR / Smart / Full Color
S/N Ratio	> 39.1 dB
White Balance	Auto
3D-DNR	Auto
Mirror/Flip	On / Off
Video Streaming	Mainstream : 1920 x 2160 Substream : 640x720
AI Features	Human Detection Motion Detection
Audio Streaming	AAC/G711A
Audio IN	Built in MIC

Audio OUT	Built in Speaker
Button	Device Reset button
TF /SD Card	Support Max 256GB
Protocol	N1 Protocol
Slots	Nano Sim Card Slot & Micro SD Card Slot
Connection Mode	4G Network & Lan network
Light Mode	LED Flash; 4G Network not Connected LED Continue ON; 4G Network Connected
Power Input	DC Input 12V – 1A
Thunder Prevention	Standard IEC61000-4-5
Power Consumption	≤15W
Operation Temperature/Humidity	-10℃ to +50℃ / 30% to 80% RH
Storage Temperature/Humidity	-20℃ to +60℃ / 20% to 90% RH
Dimension	167 x 158 x 190mm(L×W×H)
Housing Type	Plastic Housing
Weight Net	0.575Kg
Weight Gross	0.555Kg

Similar Products



4MP 4G Solar With
Battery Bullet Camera



Solar Panel
12Ah



3MP 4G Dual Lens
Mini PT Camera



3MP 4G Dual Lens
Linkage PT Camera



3MP 4G Mini PT
Camera



3MP 4G
PTZ Camera

* **Note: Product specifications are subject to change without prior notice.**