

3MP Smart 4G Dome ATC Camera



FEATURES

- 3MP (2304 x 1296) Resolution
- All Time Color Vision
- Full Duplex Audio Intercom (Built-in High Sensitivity Mic & Speaker)
- Support 10x Digital Zoom
- Area Motion Detection, Humanoid Detection, Push Raltime Notification on the Application
- Mobile Notification on Human & Motion Detection
- Customized Pre-recorded Voice Alarm
- Support Micro SD Card upto 256GB & Cloud Storage(Optional)
- Compression: H.264 / H.265 / H.265+
- 4G connection.QR code for Easy to add camera in the app
- Monitoring : Mobile/PC Software (TrueCloud)
- Alexa Support



4G SIM Support



256GB SD Card



Human Detection



Full-Duplex Audio Intercom



Voice Prompt



Works with Alexa



Onvif

Technical Specifications

Product Code	T18185-A
Image Sensor	1/2.8" CMOS Sensor
Resolutions	3MP (2304 x 1296)
Lens	4mm
IR LED	4 IR Array
IR Distance	20 Meters
White LED	4 White Array
White LED Distance	15 Meters
Min Illumination	Color: 0.01 Lux,Black & White: 0.001 Lux
Day & Night	IR-cut Auto ICR
Light Mode	Full Color / Infrared / Intelligent
Viewing Angle	Horizontal: 75°, Vertical: 59°, Diagonal: 88°
Video Streaming	Main Stream: 2304 x 1296 / 15 fps Sub Stream: 800 x 448 /15 fps
Audio Input/Output	Two way audio, Built in microphone and speakers
Audio Compression Standard	AAC/G711A
Zoom	10x Digital
DNR	3D Digital Noise Reduction
White Balance	Auto
WDR	D-WDR
Mirror/Flip	On / Off
Electronic Shutter	Auto

On Screen Display (OSD)	Date, Time, & Title
AI Features	Motion Detection, Human Detection.
Privacy Zone	Support 4 Zone
Monitoring	Andriod, iOS, Windows (TrueCloud)
Slots	4G Sim Card / Micro SD Card
Storage	Support Micro SD Card upto 256GB & Cloud Storage(Optional)
Protocol	N1/Onvif/rtmp/rtsp
Connection Mode	4G Sim Network / Lan Network
4G Frequency Band	FDD-LTE: B1/B3/B5/B8; TDD-LTE: B34/B38/B39/B40/B41
Button	Reset Button
Light Mode Indication	LED Blink: Not connected to Network, LED Continuous ON: Connected to Network
Connectors	RJ45 LAN connector (100 Mbps) and DC Power Input
Power Input	DC: 12V/1A (DC 2.1mm Connector)
Power Consumption	≤ 6W
Working Temperature / Humadity	0-50° C RH Less than 95% (No Condensation)
Storage Temperature / Humadity	-20° C to 60° C / 20% to 90% RH
Housing Type	Plastic
Dimension	97mm X108.4mm X 111.3mm (H x W x L)
Net Weight	214 Gms
Gross Weight	346 Gms

Similar Products



Smart 3MP 4G
Robot Camera



Smart 3MP
Battery Camera



Smart 3MP Wi-Fi
Dome Camera



Smart 3MP 4G
Bullet Camera



Smart 3MP 4G
Cube Camera



Smart 3MP 4G
Mini PT Camera

* Note: Product specifications are subject to change without prior notice.